

CP-4 FREE EXIT SYSTEM

Cartell's best automatic gate opener ever!


DIRECT REPLACEMENT FOR CP-3 WITH ADDED FEATURES!

Features:

- Lower price than previous models
- Self-contained system
- Conduit-ready housing
- Sensitivity adjustment
- Lowest standby current (30-70µA)
- Better heat resistance
- More lightning protection
- New proven digital circuit
- Weather-resistant cable
- One model, less confusion
- Industry-standard wire colors
- Universal voltage AC & DC
- Works with all gate operators
- 5 year warranty

Technical Specifications	
Power Required	8-24 VAC or 8-30 VDC
Stand-By Current	30-70 Microamps (µA)
Alarm Current	40-60 Milliamps (mA)
Relay Contacts	SPDT, floating, N.O. or N.C. (Form C)
Relay Contact Rating	1 amp/24 VDC (1 mA at 5 VDC min. load)
Relay Time	2-3 seconds
Enclosure Rating	IP67
Strength Rating	9.53 ton-force 8646 kgf
Temperature Range	-25° F. - +140° F. -32° C. - 60° C.
Dimensions	4.5 in. dia. x 2.5 in. high
Weight	5 lbs. with 100 ft. cable

CONNECTING TO GATES

POWER GATES	SOLAR GATES
 <p>RED → POWER +</p> <p>BLACK → POWER -</p> <p>WHITE → COMMON</p> <p>BLUE → EXIT N.O.</p> <p>YELLOW → EXIT N.C.</p>	<p>RED → POWER +</p> <p>BLACK WHITE → GND or COM</p> <p>BLUE → FREE EXIT or OPEN TERMINAL</p>

